

TUBE SEALERS



**RAPID SEAL II™
SE640**
PORTABLE UNIT



**RAPID SEAL II™
SE530**
MULTI-HEAD SEALER



**RAPID SEAL II™
SE540**
SPACE SAVING BENCHTOP SEALER



**RAPID SEAL II™
SE330 & SE340**
STANDARD BENCHTOP UNIT

Component processing is too important to leave to chance.

SPEED

- No warm-up required – Instant on
- Rapid Seal II Technology
- Never overheat
- Notched Seal™ for easy separation

COMPATIBILITY & RELIABILITY

- “Intelligent” RF Board – accepts and adjusts to all size blood tubing
- Legendary Genesis brand quality
- Trusted by blood banks worldwide
- 1 year warranty on parts and labor
- CE and UL compliant

VERSATILITY & SAFETY

- Standard bench-top units
- Portable units (AC/Battery)
- Space saving units
- Flexible multi-head solutions

TUBE SEALERS

WITH RAPID SEAL II TECHNOLOGY



Model		SE330	SE340	SE370	SE530	SE540	SE640
General Description		STANDARD BENCHTOP SEALER	MULTIPLE STATION BENCHTOP SEALER	BATTERY POWERED BENCHTOP SEALER	SPACE SAVING BENCHTOP SEALER	SPACE SAVING BENCHTOP SEALER	PORTABLE SEALING UNIT
Sealing Head Configuration		Fixed sealing head	Fixed and Hand-held sealing unit	Fixed and Hand-held sealing unit	Fixed sealing head	Fixed and Hand-held sealing unit	Hand-held sealing unit
Special Features		- Retractable splash guard "Intelligent" RF Board - RAPID SEAL II seals in 0.5 to 1.2 seconds - Easy Clean head protector	- Retractable splash guard 6' standard cable "Intelligent" RF Board - RAPID SEAL II seals in 0.5 to 1.2 seconds - Easy Clean head protector - Use fixed and hand-held sealing unit independently	- Retractable splash guard 6' standard cable "Intelligent" RF Board - RAPID SEAL II seals in 0.5 to 1.2 seconds - Battery Operated and rechargeable - Easy Clean head protector 2000+ Seals per full battery charge - Aluminum carrying case	- Flexible multi-head option - Splash guard "Intelligent" RF Board - RAPID SEAL II seals in 0.5 to 1.2 seconds - Custom Sealer Stand - Easy Clean head protector - Slim design to maximize available space - Flexible Head Spacing (75 / 80 / 85 / 90 mm)	- Flexible multi-head option - Splash guard "Intelligent" RF Board 6' standard cable - RAPID SEAL II seals in 0.5 to 1.2 seconds - Custom sealer stand - Easy Clean head protector - Slim design to maximize available space - Flexible Head Spacing (75 / 80 / 85 / 90 mm)	6' standard cable - RAPID SEAL II seals in 0.5 to 1.2 seconds - Hand Sealing Unit - Battery operated and rechargeable - Lightweight canvas carrying bag included - Medical device classified* 1000+ Seals per full battery charge
DIMENSIONS	Main Unit	6.9W x 6.1H x 13D 176W x 156H x 331D	6.9W x 6.1H x 13D 176W x 156H x 331D	6.9W x 6.1H x 13D 176W x 156H x 331D	2.9W x 9.7H x 12.8D 74W x 248H x 326D	2.9W x 9.7H x 12.8D 74W x 248H x 326D	6.1W x 1.5H x 14.4D 156W x 37H x 265D
	Hand Held Sealing Unit	N/A	1.1W x 1.8H x 8.1D 28W x 44H x 204D	1.1W x 1.8H x 8.1D 28W x 44H x 204D	N/A	1.1W x 1.8H x 8.1D 28W x 44H x 204D	1.1W x 1.8H x 8.1D 28W x 44H x 204D
	Unit	11.0 lbs 5.0 Kg	11.0 lbs 5.0 Kg	11.0 lbs 5.0 Kg	9.7 lbs 4.4 Kg	9.7 lbs 4.4 Kg	4.0 lbs 1.8 Kg
	Sealing Gun	N/A	0.5 lbs 0.2 Kg	0.5 lbs 0.2 Kg	N/A	0.5 lbs 0.2 Kg	0.5 lbs 0.2 Kg
Power Type		A/C	A/C	Battery Operated	A/C	A/C	Battery Operated
Power Source		100-240 V 50/60 Hz	100-240 V 50/60 Hz	12V / 10AH NiMH Battery (rechargeable)	100-240 V 50/60 Hz	100-240 V 50/60 Hz	12V / 4.5AH NiMH Battery (rechargeable)
Max Tubing Dia.		6 mm (1/4")	6 mm (1/4")	6 mm (1/4")	6 mm (1/4")	6 mm (1/4")	6 mm (1/4")
Remarks		—	—	—	 The 530 & 540 sealers can be used stand alone or linked as a multi-head sealing unit. Link 3, 4, 5, 6 or more units together (High Volume Use)		*Approved for use during a standard donation or apheresis procedure.

*All devices are CE and UL compliant.